

## MEGAMAN® OSTEE

### LED Liner Light

MEGAMAN® OSTEE pendant light provides a simple, bright and efficient lighting application. High quality aluminum housing and PC difussor,color custom. It can be realized through accessories, linear connection, L-shaped, T-shaped, X-shaped connection adopts with no dark area.



Line Connection



L/T Connection



Switch color temperature



## Product Features

- Stretch aluminum bracket, high strength, excellent heat dissipation performance
- Several surface treatment and color optional, beautiful and generous
- Messenger wire installation, simple operation
- Can be continuous stitching(Line/Type L/Type T/Type +), no obvious stitching dark area
- Back-lit, luminous uniform without dark area
- High luminous efficiency, up to 110lm/W
- No UV, infrared radiation, no mercury environmental protection

## Applications

- ✗ Office
- ✗ Conference Room
- ✗ Home
- ✗ Shopping mall



60°  
Beam Angle



170-240V  
Input Voltage




35000hrs  
Long Lifespan

Model No.	Wattage (W)	Luminous Flux (lm)	Luminous Efficacy (lm/W)	Dimension (L*W*H mm)	Beam Angle (°)	Power Factor (λ)
MDL1018 30W	30	3000[3000K] 3300[4000/6500K]	100(3000K) 110(4000K/6500K)	600*50*50	120	0.9
MDL1018 60W	60	6000[3000K] 6600[4000/6500K]	100(3000K) 110(4000K/6500K)	1200*50*50	120	0.9
MDL1018 CCT 30W	30	3000[3000K] 3300[4000/6500K]	100(3000K) 110(4000K/6500K)	600*50*50	120	0.9
MDL1018 CCT 60W	60	6000[3000K] 6600[4000/6500K]	100(3000K) 110(4000K/6500K)	1200*50*50	120	0.9

## General Information

Input Voltage / Frequency	170-240 VAC~ 50/60Hz
Power Factor	>0.9
Dimmability	Non-Dim
CRI	>Ra80
Colour Consistency	≤5
Lifetime	35000hrs L70B50@Ta25°C
IP	IP20
Protection Class	CL I
Glow Wire	750
Flickering Percentage	≤3% @100Hz
Material & Colour	Aluminium+Polycarbonate
Installation	Fixed/Pendant

## Photometric Data



## Dimensional Drawing

